



Battery Specifications

MODEL NUMBER	NOMINAL VOLTAGE (V)	RATED CAPACITY		NOMINAL DIMENSIONS (IN)				NOMINAL WEIGHT (LBS)	INTERNAL RESISTANCE (MILLIOHMS)	SHORT CIRCUIT CURRENT (AMPS)	TERMINAL TYPE
		15 MIN. WPC 1.67 VPC	20 HR (AH) 1.80 VPC	LENGTH	WIDTH	HEIGHT	TERMINAL HEIGHT				
S12V325FL	12	324.9	82	10.24	6.61	8.19	8.31	52.9	4.5	1640	T6
S12V370FL	12	370.3	95	12.05	6.61	8.15	8.27	61.7	4.0	1900	T6
S12V539FL	12	539.0	155	13.19	6.77	10.83	10.95	93.5	3.1	3100	T8

Terminal Specifications

T6 TERMINAL	Threaded insert: tin plated copper alloy 6mm bolt torque: 71 in-lb	T8 TERMINAL	Threaded insert: tin plated copper alloy 6mm bolt torque: 71 in-lb
			

Discharge Performance (Constant Power Discharge)

1.85V PER CELL - CONSTANT POWER (WATTS/CELL) DISCHARGE @ 25°C							
Model	5 min	10 min	15 min	20 min	30 min	60 min	90 min
S12V325FL	345.5	267.9	247.8	217.9	168.9	102.5	76.4
S12V370FL	408.1	334.7	286.3	243.4	188.8	113.2	86.0
S12V539FL	537.7	438.4	382.7	337.8	271.0	172.5	130.8
1.80V PER CELL - CONSTANT POWER (WATTS/CELL) DISCHARGE @ 25°C							
Model	5 min	10 min	15 min	20 min	30 min	60 min	90 min
S12V325FL	392.4	292.3	269.0	232.7	176.4	105.2	78.4
S12V370FL	452.1	369.2	308.6	260.6	198.3	117.7	88.1
S12V539FL	615.4	480.8	417.8	371.3	293.0	181.3	136.8
1.75V PER CELL - CONSTANT POWER (WATTS/CELL) DISCHARGE @ 25°C							
Model	5 min	10 min	15 min	20 min	30 min	60 min	90 min
S12V325FL	441.8	325.1	290.0	244.5	182.2	107.2	80.0
S12V370FL	499.6	401.3	330.8	276.0	206.7	121.6	90.5
S12V539FL	710.1	530.7	458.9	398.9	312.2	190.2	142.9
1.70V PER CELL - CONSTANT POWER (WATTS/CELL) DISCHARGE @ 25°C							
Model	5 min	10 min	15 min	20 min	30 min	60 min	90 min
S12V325FL	480.7	348.5	305.4	257.5	189.6	109.5	81.4
S12V370FL	547.6	430.4	348.0	290.7	214.9	124.3	92.2
S12V539FL	785.4	577.9	499.2	430.2	332.1	197.9	148.0
1.67V PER CELL - CONSTANT POWER (WATTS/CELL) DISCHARGE @ 25°C							
Model	5 min	10 min	15 min	20 min	30 min	60 min	90 min
S12V325FL	527.5	376.7	324.6	267.6	196.7	112.0	83.0
S12V370FL	600.7	457.2	370.3	304.6	223.9	127.2	94.0
S12V539FL	852.0	630.1	539.0	454.3	344.4	203.8	152.3
1.60V PER CELL - CONSTANT POWER (WATTS/CELL) DISCHARGE @ 25°C							
Model	5 min	10 min	15 min	20 min	30 min	60 min	90 min
S12V325FL	573.4	402.2	339.1	279.0	202.3	113.5	84.0
S12V370FL	644.5	482.0	385.7	315.2	229.1	130.2	96.1
S12V539FL	908.9	667.5	558.6	468.8	354.4	207.5	154.5

Discharge Performance (Constant Current Discharge)

1.75V PER CELL - CONSTANT CURRENT (AMPS) DISCHARGE @ 25°C							
Model	5 min	10 min	15 min	20 min	30 min	60 min	90 min
S12V325FL	231.8	169.5	150.2	126.0	93.3	54.3	40.5
S12V370FL	262.2	209.2	171.4	142.2	105.8	61.6	45.7
S12V539FL	381.3	281.8	241.2	207.9	161.8	97.3	73.0
1.70V PER CELL - CONSTANT CURRENT (AMPS) DISCHARGE @ 25°C							
Model	5 min	10 min	15 min	20 min	30 min	60 min	90 min
S12V325FL	255.2	183.7	160.1	134.1	98.1	55.9	41.5
S12V370FL	290.7	226.9	182.4	151.3	111.2	63.5	47.0
S12V539FL	425.9	309.7	265.0	225.9	173.3	102.0	76.1
1.67V PER CELL - CONSTANT CURRENT (AMPS) DISCHARGE @ 25°C							
Model	5 min	10 min	15 min	20 min	30 min	60 min	90 min
S12V325FL	282.3	200.1	171.2	140.2	102.3	57.5	42.5
S12V370FL	321.5	242.8	195.3	159.6	116.5	65.3	48.2
S12V539FL	466.9	341.3	288.5	240.4	180.8	105.6	78.7
1.60V PER CELL - CONSTANT CURRENT (AMPS) DISCHARGE @ 25°C							
Model	5 min	10 min	15 min	20 min	30 min	60 min	90 min
S12V325FL	310.4	215.9	180.7	147.6	106.3	58.8	43.4
S12V370FL	348.8	258.8	205.6	166.7	120.4	67.5	49.7
S12V539FL	507.8	369.2	304.4	253.4	190.0	109.5	81.3

Product Description

CONSTRUCTION	
Positive Plate	Lead-calcium grids minimize corrosion & prolong life
Negative Plate	Balanced lead-calcium grids optimize recombination efficiency
AGM Separator	Mechanically strong, low electrical resistance, micro porous glass fiber which completely absorbs the electrolyte into its structure
Terminal Post	Threaded copper alloy terminals for maximum conductivity
Venting Valve	EPDM Rubber 0.44 ~2.18 PSI resealing pressure. Releasing at 1.45~5.08 PSI.
Container	ABS - Flame Retardant Containers to UL94V-0 is standard.

OPERATION TEMPERATURE RANGE	
Nominal	20°C ~ 25°C (68°F ~ 77°F)
Discharge	-20°C ~ 55°C (-4°F ~ 131°F)
Charge	0°C ~ 50°C (32°F ~ 122°F) With temperature compensated charger
Storage	-20°C ~ 55°C (-4°F ~ 131°F)

PERFORMANCE	
Recommended Maximum Charging Current Limit	Less than 0.3C A
Float Charging Voltage	13.5V ~ 13.8V at 25°C, Temp. Coefficient -20mV/°C
Maximum AC Ripple (Charger)	±0.02v/cell
Self-Discharge	Low self-discharge rate less than 3% / month @20°C
Equalize Charge and Cycle Service Life Voltage	14.1 ~ 14.4V for equalize charge and 14.4 ~ 15.0V for cycle charge voltage @25°C